

OPTIMUM SEISMIC PROTECTION FOR NEW BUILDING  
CONSTRUCTION IN EASTERN METROPOLITAN AREAS

NSF Grants GK-27955 and GI-29936

Internal Study Report No. 27


[DAMPING CAPACITY OF BOSTON BLUE CLAY

Paul J. Trudeau

Any opinions, findings, conclusions  
or recommendations expressed in this  
publication are those of the author(s)  
and do not necessarily reflect the views  
of the National Science Foundation.

January 1973

Department of Civil Engineering  
Massachusetts Institute of Technology  
Cambridge, Massachusetts



<b>REPORT DOCUMENTATION PAGE</b>	<b>1. REPORT NO.</b> NSF-RA-E-73-540	<b>2.</b>	<b>3. Recipient's Accession No.</b> PD294050
<b>4. Title and Subtitle</b> Damping Capacity of Boston Blue Clay (Optimum Seismic Protection for Low Building Construction in Eastern Metropolitan Areas), Internal Study Report 27		<b>5. Report Date</b> January 1973	
<b>7. Author(s)</b> P.J. Trudeau		<b>6.</b>	
<b>9. Performing Organization Name and Address</b> Massachusetts Institute of Technology Department of Civil Engineering Cambridge, Massachusetts 02139		<b>8. Performing Organization Rept. No.</b> Internal Study Report 27	
<b>12. Sponsoring Organization Name and Address</b> Applied Science and Research Applications (ASRA) National Science Foundation 1800 G Street, N.W. Washington, D.C. 20550		<b>10. Project/Task/Work Unit No.</b>	
<b>15. Supplementary Notes</b>		<b>11. Contract(C) or Grant(G) No.</b> (C) (G)GI29936, GK27955	
<b>16. Abstract (Limit: 200 words)</b> This report presents the results of the determination of the damping capacity of undisturbed samples of Boston Blue Clay obtained using Massachusetts Institute of Technology's Hardin Oscillator. Two methods of determining damping were used and are illustrated. In the Log Decrement method a photograph of the decaying vibration is used to determine the log decrement of the apparatus and of the system with specimen at the resonant frequency. Equations are then used to compute the damping ratios. In the Frequency and Amplitude of Vibration method, the frequencies and amplitudes of vibration at resonance and at a higher frequency are used to determine the damping capacity. The values of damping of Boston Blue Clay as determined by this testing program are between 1 percent and 3 percent.		<b>13. Type of Report &amp; Period Covered</b>	
<b>17. Document Analysis a. Descriptors</b> Earthquake resistant structures                      Soil dynamics                      Soil tests Damping capacity    Soil properties                      Clay soils		<b>14.</b>	
<b>18. Availability Statement</b> NTIS		<b>19. Security Class (This Report)</b>	<b>21. No. of Pages</b> 11
		<b>20. Security Class (This Page)</b>	<b>22. Price</b> A02-A01

CAPITAL SYSTEMS GROUP, INC.  
6110 EXECUTIVE BOULEVARD  
SUITE 250  
ROCKVILLE, MARYLAND 20852

## List of Internal Study Reports

1. "Preliminary Work Plans and Schedules"
2. "Background for Preliminary Expected Future Loss Computations"
3. "Identification of Typical Soil Profiles in the Boston Basin Area"
4. "Comparison of Wind and Seismic Forces on Tall Buildings"
5. "Contribution to State-of-the-Art Report of the Earthquake Committee of the IABSE-ASCE Tall Buildings Committee -- Economic and Social Aspects"
6. "Optimum Seismic Protection for New Building Construction in Eastern Metropolitan Areas"
7. "Analysis of the Seismic Risk on Firm Ground for Sites in the Central Boston Metropolitan Area"
8. "1967 Caracas Venezuela Earthquake Tall Building Damage Review"
9. "Damage Statistics from Japanese Earthquakes"
10. "Evaluation of Expected Losses and Total Present Cost: Preliminary Sensitivity Analysis"
11. "1964 Alaskan Earthquake Tall Building Damage Review"
12. "San Fernando Earthquake Data Base Computer Storage Format"
13. "San Fernando Earthquake Damage Statistics"
14. "Elastic Analysis of Pilot Building"
15. "Soil-Amplification Analyses on Typical Boston Soil Profiles"
16. "Description and User's Manual of the Inelastic Dynamic Analysis Program"
17. "Ground Motions Measured by VM-1"
18. "Borings on MIT Campus near Westgate II"
19. "Evaluation of Expected Losses and Total Present Cost: Further Preliminary Sensitivity Analyses"
20. "Damage Prediction of Three Types of Buildings Based on Dynamic Analysis"
21. "Incident Losses: Identification and Evaluation Methods to be Employed"
22. "1957 San Francisco Earthquake Tall Building Damage Review"
23. "1965 Puget Sound, Washington, Earthquake Tall Building Damage Review"
24. "Evaluation of Risky Public Projects"
25. "Microtremor Measurements in the Boston Area"
26. "In Situ Shear Wave Velocity Measurements on MIT Campus"

## DAMPING CAPACITY OF BOSTON BLUE CLAY

This report presents the results of the determination of the damping capacity of Boston Blue Clay obtained using MIT's Hardin Oscillator. For a description of the testing program see Trudeau (1973). The procedures used in calculating the damping capacity are outlined in Hardin (1970). A sample calculation for Test G-1 is included in Appendix A of this report.

These tests were performed on undisturbed samples of Boston Blue Clay. The purpose of these tests was to determine the shear wave velocity of Boston Blue Clay to be used in soil amplification studies in the design of structures in the Boston area against earthquakes; however, values of damping capacity of the specimens tested were also obtained. Inexperience and faulty electronic equipment led to erroneous values of damping for the earlier tests. However, the values of damping reported in Table 1 were obtained after the electronic equipment was repaired and more experience had been gained. Therefore, it is the opinion of the author that these values are good.

Two methods of determining damping were used and are illustrated in Appendix A. In the Log Decrement method a photograph of the decaying vibration is used to determine the log decrement of the apparatus and of the system (with specimen) at the resonant frequency. Equations presented in Hardin (1970)

are then used to compute the damping ratios. In the Frequency and Amplitude of Vibration method, the frequencies and amplitudes of vibration at resonance and at a higher frequency (equal to  $f_n^2 / f_0$ ) are used to determine the damping capacity.

As can be seen in Table 1, the values of damping of Boston Blue Clay as determined by this testing program are between 1 and 3%. The values for Tests L-1 and AA-1 of 1-1.5% were obtained after an elapsed time of approximately one day whereas the values of 3% for Test G-1 were obtained after four days of testing. Past testing of clay soils (Hardin and Drnevich, 1972; and Richart, Hall, and Woods, 1970) has indicated damping ratios within this range; therefore, these values appear to be reasonable.

## LIST OF REFERENCES

- Hardin, Bobby O., "Suggested Methods of Test for Shear Modulus and Damping of Soils by the Resonant Column," ASTM, STP 479, pp. 516 - 529, 1970.
- Hardin, Bobby O., and Drnevich, V. P., "Shear Modulus and Damping in Soils: Measurement and Parameter Effects," JSMFD, ASCE, Volume 98, SM 6, June, 1972.
- Richart, F. E., Jr.; Hall, J. R., Jr.; and Woods, R. D.; Vibrations of Soils and Foundations, Prentice - Hall, New Jersey, 1970.
- Trudeau, P. J., "The Shear Wave Velocity of Boston Blue Clay," MIT Department of Civil Engineering Research Report R73 -12, Soils Publication # 317, 1973.



DAMPING CAPACITY  
OF  
BOSTON BLUE CLAY

TABLE I

TEST	LOG DECREMENT	FREQ. & AMP. OF VIBRATION	ELAPSED TIME
	%	%	DAYS
L-1	1.20	1.02	1
AA-1	1.57	1.41	1
G-1	2.91	2.92	4

NOTE: VALUES OBTAINED  
AT IN SITU  $\bar{\sigma}_{OCT}$

# APPENDIX A

## CALCULATION OF DAMPING FOR TEST G-1

## CALCULATION OF DAMPING FOR TEST G-1

$$S = \frac{2 K_o L}{\pi C_m G_{ksc} r^4 981 \times 10^3} = \frac{(2)(3.389 \times 10^9)(8.00)}{\pi (1.005)(483)(1.74)^4 981 \times 10^3}$$

$$S = 3.53$$

$$D = \frac{1}{2\pi} \left[ \delta_s (1+S) - \delta_A S \right] \times 100\%$$

$$\delta_A = 0.029 \quad \delta_s = 0.063$$

$$\rightarrow D = 2.91\%$$

LOG  
DECREMENT

## CALCULATION OF DAMPING FOR TEST G-1

$$T_n = 4.787 \text{ m SEC} \rightarrow f_n = 208.9 \text{ CPS}$$

$$T_o = 5.33 \text{ m SEC} \rightarrow f_o = 187.6 \text{ CPS}$$

$$\frac{f_n}{f_o} = 1.114 \rightarrow C_1 = 0.867 \quad C_2 = 1.25$$

$$R = \frac{A_{T_n}}{A_{T_1}} = \frac{27.0}{2.95} = 9.15$$

$$D = \frac{1}{2} \left[ \frac{C_1}{R} - C_2 S_A \right] \times 100\%$$

$$\rightarrow D = 2.92 \%$$

FREQUENCY AND AMPLITUDE  
OF VIBRATION